

■ Terminal Blocks

● Combination terminal blocks

| Type | Withstand voltage [V] | Rated current [A] | Connecting wire size | CSA File No. |
|-----------|-----------------------|-------------------|----------------------|--------------|
| LT2F-010 | 600 | 15 | 20-16 AWG-Cu | LR702989 |
| LT2F-020 | | 19 | 16-14 AWG-Cu | |
| LT2F-030 | | 27 | 14-10 AWG-Cu | |
| LT2F-040 | | 35 | 12-10 AWG-Cu | |
| LT2F-080 | | 68 | 6-8 AWG-Cu | |
| LT2F-020W | | 19 | 18-14 AWG-Cu | |
| LT2E-020 | | 20 | 20-14 AWG-Cu | |
| LT2E-030 | | 30 | 18-12 AWG-Cu | |
| LT2E-040 | | 40 | 18-10 AWG-Cu | |
| LT2E-080 | | 75 | 10-6 AWG-Cu | |
| LT2E-090 | | 95 | 8-4 AWG-Cu | |
| LT2E-150 | | 150 | 4-2/0 AWG-Cu | |
| LT2E-200 | | 200 | 2-4/0 AWG-Cu | |
| LT2E-300 | | 300 | 2/0-300 AWG-Cu | |
| LT2E-400 | | 400 | 4/0-350 AWG-Cu | |
| LT2E-600 | | 550 | 300-600 AWG-Cu | |

● Relaying connector terminal blocks

CSA approved products are the same as UL approved ones. For details, see the following documents:

| LP5W series | |
|----------------|--------|
| CSA File No. | E45457 |
| Reference page | 46 |